

Application area	Category	Order code
Facility Automation / Smart Living	multifunctional sensor KNX	4260220541127

**Productname**



The multi functional sensor Motion 360 KNX is suitable for ceiling mount. It monitors movement, brightness and temperature with a detection angle of 360°. The Motion 360 KNX comes with two dry contacts and several logic functions.


**Technical data**

Power supply	
Bus operating voltage:	DC 21-30V
Consumption of electricity:	15mA / DC 24V
Physical connections	
Input:	DC 24V
KNX connection:	KNX bus-clamp (red/grey) 0.8mm <sup>2</sup>
Supply line:	for cables up to 2.5 mm <sup>2</sup>
Inputs:	two dry contacts
Communication	
KNX/EIB	
Construction	
Body material:	plastic white
Size:	80x80x30mm
Weight:	60g
Mounting:	ceiling mount
Package size:	90x94x45mm
Shipping weight:	90g
Environmental conditions	
Working temperature:	-5°C ~ +45°C
Storage temperature:	25°C ~ +55°C
Relative humidity:	max. 95%

**Functions**

- Luxmeter:**  
Measures the brightness of the room to control the lighting and dimming system
- Motion Detection:**  
The sensor reacts to movements in the room and switches various functions
- Additional dry contacts:**  
Include other life-saving or security dedicated sensors to your KNX EIB. BUS system and save cable while increasing the ability and overall function. glassbroke sensors, fire detectors, smoke detectors, door and window contacts and many more.
- Integrated logic functions:**  
Measure results can be smartly combined. Complex scenarios can be programmed with simple „if/then“ commands.
- Temperature sensor**

**Detection angle**



**Dimensions**

